

METHOD AND SYSTEM FOR PROCESSING A THREE-DIMENSIONAL SHAPE DATA

This application is based on Japanese Patent Application
5 No. 372356/1999 filed on December 28, 1999, the contents of
which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to a method and a system
for processing a three-dimensional shape data.

Description of Prior Art

Conventionally, modeling which utilizes a three-
dimensional measuring apparatus is performed. For example, a
15 three-dimensional measuring apparatus using a light-section
method, scans optically an object by projecting and deflecting a
slit light and calculates a three-dimensional shape data by
applying a principle of a triangular surveying. Such
measurement is performed around the object, a plurality of the
20 obtained three-dimensional shape data are connected together,
so as to obtain the shape model for the object as a whole.

Because of the measuring conditions, such as shape or
direction of an object, or lighting, the three-dimensional shape
data sometimes cannot be obtained perfectly, the lack of the data
25 may occur. In this case, the filling of the lack part, namely the
data correction of the three-dimensional shape data is
performed.

Conventionally, as a method for filling the portion with
lack of data, the method of using a grid as a fundamental model,
30 generating a new curved surface by transforming the grid, and

connecting the generated surface with the outline of the portion
with lack of data is provided. The unexamined Japanese patent
publication No. 11-15994 discloses a computer system in which
an operator can adjust the curved surface by trial and error with
5 monitoring the result so as to make the filling natural. In this
system, by designating at least one point inside the curved
surface and a target position, the curved surface is automatically
modified to be smooth surface including the target position,
automatically, and the numerical data representing the change of
10 the shape is displayed. The operator evaluates the modification
by the numerical data, if the operator is not satisfied with the
result, then he or she designates again a point inside the curved
surface and a target position.

Conventionally, there is a problem that the operator must
15 designate a large number of values for adjusting the curved
surface to be added to the shape model and the data correction
operation of the shape model is troublesome. Especially, if the
shape model has a complex surface with ups and downs, the
operator must designate many points, therefore the load on the
20 operator is heavy.

SUMMARY OF THE INVENTION

The object of the present invention is to provide a
method and system for adding a required curved surface to a
25 portion of the shape model by a simple and easy input operation.

According to an aspect of the present invention, a method
comprises the steps of obtaining three-dimensional shape data
representing a three-dimensional shape model, designating a
portion of the three-dimensional shape model required to be
30 corrected, displaying a surface to be joined to the designated

portion, modifying a shape of the surface corresponding to an alteration of a parameter, and re-displaying the modified surface in response to the reception of alteration.

According to another aspect of the present invention, a method comprises the steps of displaying a three-dimensional shape model and a surface to be joined to the three-dimensional shape model, the shape of the surface is defined by at least one parameter, obtaining only one value of the parameter, and modifying the displayed surface based on the obtained value of the parameter.

The other objects and features of the present invention will be more fully understood from the following detailed description with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a three-dimensional processing apparatus according to an embodiment of the present invention;

Fig. 2 is a schematic diagram for illustrating a filling process;

Fig. 3A is a diagram for showing a form of a dialogue of a first operation example;

Fig. 3B is a diagram for illustrating a changing of a displayed monitor image of the first operation example;

Fig. 4A is a diagram for showing a form of a dialogue of a second operation example;

Fig. 4B is a diagram for illustrating a changing of a displayed monitor image of the second operation example; and

Fig. 5 is a diagram for illustrating a data processing for filling of a lack portion.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 is a block diagram showing a configuration of a three-dimensional processing system of an embodiment according to the present invention.

Referring to Fig. 1, the three-dimensional processing system 1 is a computer system which comprises a bus 10, a CPU (central processing unit) 11, a memory 12, an auxiliary storage device 13, an input/output interface 14, a keyboard 15, a mouse 16, and a display 17.

The CPU 11 executes various processes including a data modification according to the present invention. The memory 12 includes a ROM 12a for storing a control program in which a sequence executed by the CPU 11 is scripted, and a RAM 12b providing a data storage area and a working area required for the execution of the various processes by the CPU 11. The auxiliary storage device 13 is used for storing an objective data such as a three-dimensional data (shape data), a two-dimensional color image data, and so forth. The input/output interface 14 is used for inputting an objective data from the external of the device or for outputting a generated data to the external of the device.

The keyboard 15 and the mouse 16 are used for inputting various instructions or settings. The display 17 displays images of three-dimensional data and the generated surface, and also is used for displaying a processing status, a processed result, and a progressing status. The display 17 can display a plurality of windows by a multi-window system.

By using the three-dimensional processing system 1, a required curved surface data can be added to a three-dimensional

data which is either inputted from the three-dimensional measuring apparatus (not shown), or generated by the modeling process. This function is suitable for a full-filled process of a lack portion (hole) of a shape model.

5 Fig. 2 is a schematic diagram of a filling process.

The three-dimensional data as an object for correction shown in the example is a shape model M of a mascot doll. The lack portion 90 exists in the shape model M. Namely, the mascot doll M lacks the upper side surface portion. The-
10 filling-a-hole process is a data processing such that a grid-like plane surface m is attached on a lack portion 90, the plane surface m is modified to an appropriate curved surface corresponding to the shape model M, so as to join the curved surface to the outline of the lack portion. Thus, with the three-
15 dimensional processing system 1, an operator (user) can fill the lack portion with the desired curved surface by a simple and easy operation.

[First operation example]

Figs. 3A and 3B are diagrams showing a first operation
20 example. Fig. 3A shows a form of a dialogue window and Fig. 3B shows a changing of an image on a monitor display.

An operation sequence of the first example is as follows:

(1) In the modeling mode capable of correcting the shape model M, an operator instructs to execute filling a hole with
25 designation of the area which contains a lack portion 90. Thus, the three-dimensional processing system 1 specifies an object of a process by detecting an outline of the lack portion 90, and displays a dialogue window 71 for querying a parameter value (coefficient γ , mentioned later) onto a screen of a display 17.

30 (2) The operator fixes (designates) a parameter value

between a range of 0-1 by dragging a knob 714 of a slider in the
dialogue window 71. Then, the operator clicks an "Apply"
button 711. The three-dimensional processing system 1
performs a calculation for filling a hole, and displays an image
5 G4 showing a result of filling on a monitor area 75 in the screen.
This calculation process corresponds to a first step of the
present invention and displaying of the result corresponds to a
second step. The image G4 shows a condition that the curved
surface m4 is positioned on the shape model M. A curvature of
10 the curved surface m4 is defined by the parameter value.

(3) When a sufficient result could not be obtained, the
operator resets appropriately the parameter value, and clicks the
"Apply" button 711 again. The operator repeats this operation
until the sufficient shape is obtained. In response to the
15 modification of the parameter value, the three-dimensional
processing system 1 recalculates and displays the result. This
process corresponds to a third step of the present invention. In
the example shown in Fig. 3B, after displaying the image G4, the
parameter is modified twice in total, the displayed image is
20 changed from the image G4 to an image G2, and further from the
image G2 to an image G3, according to the modification of the
parameter. Thus, by making the parameter value larger than
that of the curved surface m4, the curved surface m2 having a
more gentle curve than that of the surface m4 is applied, and by
25 selecting the parameter value between the surface m4 and the
surface m2, the curved surface m3 having a curve more gentle
than the surface m4 and sharper than the surface m2 is applied.

Each of images G2, G3, and G4 is obtained by projecting
the shape model located in the virtual space onto the screen.
30 The operator can select a display mode such as a surface model

to which a shading is applied, a wire frame model, and the like.

(4) If the sufficient result is obtained, an "OK" button 712 is clicked. Thus, the filling-a-hole process is completed. The shape model filled is stored in the auxiliary storage device 13 as the result corrected three-dimensional data.
[Second operation example]

Figs. 4A and 4B are diagrams showing a second operation example. Fig. 4A shows a form of a dialogue window and Fig. 4B shows a changing of an image on a monitor display.

An operation sequence of the second example is as follows:

(1) In the modeling mode, an operator instructs to execute filling a hole with the designation of the area which contains a lack portion 90. Thus, the three-dimensional processing system 1 specifies an object of a process by detecting an outline of the lack portion 90, and calculates for a filling process by applying a default value of the parameter (e.g., 0.5). The three-dimensional processing system 1 displays an image G3 showing a result of the filling process on a monitor area 75 in the screen and displays a dialogue window 72 for querying whether a parameter value is appropriate.

(2) The operator can fix a parameter value between a range of 0-1 by dragging a knob 724 of a slider in the dialogue window 72. In response to dragging, the calculation for filling a hole is performed by applying the parameter value of the dragged portion, and the result images G1-5 are displayed in real time. Thus, only by operating the slider, the shape of a filled portion can be changed freely either to be flat or sharp.

(3) If the sufficient result is obtained, an "OK" button 722 is clicked. Thus, the filling-a-hole process is completed.

With such a second operation, the operation of the filling process can more rapidly proceed than the first operation. However, this operation requires that the process performances of the devices including CPU11 are sufficiently high.

5 Hereinafter described the calculation for the filling process.

As shown in Fig. 5A, it is considered that an x-y plane along with the lack portion (hereinafter refers to as a "hole") 90 and z direction perpendicular to the x-y plane is set as the
10 direction for attachment, plane (grid) m which is larger than the hole 90 is prepared and applied to the hole 90. Moving the grid points inside the hole 90 in the z direction generates the curved surface. When positioning of each grid point of the plane m, an influence of the position (inclination) of the data of the
15 periphery of the hole 90 in the shape model M is considered. Therefore, the grid points are calculated to minimize a sum up to the second order differentiation among the interpolation points on the boundary condition of data position of a periphery of the hole. Thus, by changing coefficients of terms of a first order
20 differential and a second order differential, the shape of the generated curved surface can be changed, and the filling process according to the intention of the user can be achieved.

As shown with a wide frame line in Figs. 5A and 5B, a bounding box BB is generated on the hole 90. The grid is
25 formed within the bounding box BB and also outside of the bounding box BB the grid is formed by 1 line around it. The number of the grid point is automatically calculated from the three-dimensional data on the periphery of the hole 90. The user can also designate the number of the grid points.

30 The curved surface is generated by calculating the

position of the grid points inside the hole 90 (white circle ○ of Figs. 5A and 5B) in the z direction. Those grid points are unknown data. The grid points which exist inside the bounding box BB and outside the hole 90 (dark circle ● of Figs. 5A and 5B) are known data, and those are used as boundary values for connecting the shape model M with the curved surface. The grid points outside the hole 90 on the bounding box BB (dark square ■ of Figs. 5A and 5B) are boundary values. These boundary values can be obtained by projecting the grid points to a polygon of the shape model M.

These boundary values, known data, and unknown data are two-dimensional array as $u_{y, x, y=0, \dots, N_y+3, x=0, \dots, N_x+3}$ (where N_x and N_y are the number of the grid points in the x direction and y direction, respectively, inside the bounding box BB). The boundary values and the known data are already
15 obtained. The grid intervals in the x direction and y direction are H_x and H_y , respectively.

To obtain unknown data, an energy function is determined and the unknown data can be determined to minimize the energy function.

$$E(u) = S(u) + P(u)$$

where $S(u)$ represents the degree of less smoothness, and $P(u)$ represents a gap from the restriction condition.

S(u) is represented by the sum of the first order
25 differentiation and the second order differentiation, and P(u) is
not considered.

Therefore:

(Expression 1)

$$S(u) = \frac{1}{2} \left\{ \gamma \sum_i^{N_y+2} \sum_j^{N_x+2} [(u_{i,j}^x)^2 + (u_{i,j}^y)^2] + (1-\gamma) \sum_i^{N_y+2} \sum_j^{N_x+2} [(u_{i,j}^{xx})^2 + 2(u_{i,j}^{xy})^2 + (u_{i,j}^{yy})^2] \right\}$$

$$P(u) = 0$$

In $S(u)$, if the coefficient γ of the first order differential term is near 1, the influence of the first order differential term becomes remarkable. Therefore, the curvature of the generated curved surface becomes small and flat. On the contrary, if the coefficient γ of the first order differential term is near 0, the influence of the second order differential term becomes remarkable. Therefore, the curvature of the generated curved surface becomes large.

Then, the u_0 is calculated to minimize the energy function $E(u)$. If $u=u_0$, minimum $E(u)$ can be obtained,
$$\nabla E(u_0) = \nabla S(u_0) = 0.$$

By expanding this, the primary simultaneous equation can be obtained. The unknown data is derived as a solution of the primary simultaneous equation. The curved surface can be generated by the derived unknown data. By modifying the value of γ , filling the user's desires can be achieved. By generating the curved surface using only unknown data, and connecting the generated surface with the outline of the hole 90, then the filling process is completed.

In the embodiments described above, the parameter defining the curvature corresponding to one input item can be plural (for example, independent parameters are used in the x axis direction and y axis direction). The graphical user interface for modifying the operation of the parameter is not limited to slider and thus a dial-like member can be used.

According to the embodiments described above, desired curved surface can be added to a part of the shape model by the simple and easy operation.